



BSP Wartelkoppeling met 60° conus type BF



Modellen:

Bestelnummer	slangmaat	F	H	L	S	max. werkdruk bar*
C02BF-03	3/16	1/8	16	41	14	350
C04BF-03	3/16	1/4	19	44	19	415
C02BF-04	1/4	1/8	17	45	14	350
C04BF-04	1/4	1/4	19	47	19	450
C06BF-04	1/4	3/8	22	50	22	450
C08BF-04	1/4	1/2	23	51	27	450
C04BF-05	5/16	1/4	19	47	19	350
C06BF-05	5/16	3/8	22	50	22	350
C08BF-05	5/16	1/2	23	51	27	350
C04BF-06	3/8	1/4	19	49	19	445
C06BF-06	3/8	3/8	21	51	22	445
C08BF-06	3/8	1/2	23	54	27	415
C06BF-08	1/2	3/8	22	56	22	415
C08BF-08	1/2	1/2	23	56	27	415
C10BF-08	1/2	5/8	23	59	27	350
C12BF-08	1/2	3/4	27	60	32	350
C08BF-10	5/8	1/2	23	59	27	350
C10BF-10	5/8	5/8	23	59	30	350
C12BF-10	5/8	3/4	27	63	32	350
C10BF-12	3/4	5/8	24	64	30	350
C12BF-12	3/4	3/4	27	67	32	350
C16BF-12	3/4	1	30	70	41	280
C16BF-16	1	1	30	81	41	280
C20BF-16	1	1 1/4	35	86	50	250
C20BF-20	1 1/4	1 1/4	34	92	50	210
C24BF-20	1 1/4	1 1/2	36	93	55	210
C24BF-24	1 1/2	1 1/2	34	99	55	185
C32BF-24	1 1/2	2	39	103	70	185
C32BF-32	2	2	37	107	70	175

BSP 45° Wartelkoppeling met 60° conus type B45



Modellen:

Bestelnummer	slangmaat	F	H	L	K	S	max. werkdruk bar*
C02B45-03	3/16	1/8	33	58	14	14	350
C04B45-03	3/16	1/4	35	60	16	19	415
C02B45-04	1/4	1/8	36	64	16	14	350
C04B45-04	1/4	1/4	37	65	16	19	450
C06B45-04	1/4	3/8	40	68	19	22	450
C08B45-04	1/4	1/2	42	70	21	27	450
C04B45-05	5/16	1/4	39	67	18	19	350

* Attentie: let ook op de maximale werkdruk van de slang.