


Metrische koppeling uitwendige draad 24° conus type ME
DIN2353



Modellen:

Serie L							
Bestelnummer	slangmaat	leiding maat	F	H	L	S	max. werkdruk bar*
C12ME-06L-03	3/16	6L	M12X1,5	21	46	12	280
C12ME-06L-04	1/4	6L	M12X1,5	21	49	12	280
C14ME-08L-04	1/4	8L	M14X1,5	21	49	14	280
C16ME-10L-04	1/4	10L	M16X1,5	23	51	17	280
C18ME-12L-04	1/4	12L	M18X1,5	23	51	19	280
C16ME-10L-05	5/16	10L	M16X1,5	23	51	17	280
C18ME-12L-05	5/16	12L	M18X1,5	23	51	19	280
C16ME-10L-06	3/8	10L	M16X1,5	23	53	17	280
C18ME-12L-06	3/8	12L	M18X1,5	23	53	19	280
C22ME-15L-06	3/8	15L	M22X1,5	25	56	22	280
C22ME-15L-08	1/2	15L	M22X1,5	26	59	22	280
C26ME-18L-08	1/2	18L	M26X1,5	28	61	27	210
C26ME-18L-10	5/8	18L	M26X1,5	28	64	27	210
C30ME-22L-10	5/8	22L	M30X2	30	66	30	210
C26ME-18L-12	3/4	18L	M26X1,5	29	70	27	210
C30ME-22L-12	3/4	22L	M30X2	31	72	30	210
C36ME-28L-16	1	28L	M36X2	35	86	36	165
C45ME-35L-20	1 1/4	35L	M45X2	40	97	46	100
C52ME-42L-24	1 1/2	42L	M52X2	42	106	55	100
Serie S							
Bestelnummer	slangmaat	leiding maat	F	H	L	S	max. werkdruk bar*
C14ME-06S-04	1/4	6S	M14X1,5	23	51	14	450
C16ME-08S-04	1/4	8S	M16X1,5	23	51	17	450
C18ME-10S-04	1/4	10S	M18X1,5	24	52	19	450
C18ME-10S-05	5/16	10S	M18X1,5	24	52	19	350
C20ME-12S-05	5/16	12S	M20X1,5	25	53	22	350
C18ME-10S-06	3/8	10S	M18X1,5	24	55	19	445
C20ME-12S-06	3/8	12S	M20X1,5	25	56	22	445
C22ME-14S-06	3/8	14S	M22X1,5	27	58	22	445
C22ME-14S-08	1/2	14S	M22X1,5	28	61	22	415
C24ME-16S-08	1/2	16S	M24X1,5	29	62	24	415
C30ME-20S-10	5/8	20S	M30X2	32	68	30	350
C30ME-20S-12	3/4	20S	M30X2	33	74	30	350
C36ME-25S-12	3/4	25S	M36X2	37	78	36	350
C36ME-25S-16	1	25S	M36X2	39	90	36	280
C42ME-30S-16	1	30S	M42X2	43	94	46	280
C42ME-30S-20	1 1/4	30S	M42X2	44	101	46	210
C52ME-38S-20	1 1/4	38S	M52X2	48	105	55	210
C52ME-38S-24	1 1/2	38S	M52X2	48	112	55	185

* Attentie: let ook op de maximale werkdruk van de slang.