



SAE Flens 6000PSI uit een stuk type X6-ES (exclusief O-ring)



Modellen:

Bestelnummer	slangmaat	Flens	H	L	A	max. werkdruk bar*
C08X6-08 ES	1/2	1/2	47	80	31,8	415
C12X6-08 ES	1/2	3/4	47	80	41,3	415
C08X6-10 ES	5/8	1/2	48	84	31,8	350
C12X6-10 ES	5/8	3/4	48	84	41,3	350
C08X6-12 ES	3/4	1/2	50	90,5	31,8	350
C12X6-12 ES	3/4	3/4	58	98,5	41,3	350
C16X6-12 ES	3/4	1	58	98,5	47,6	350
C12X6-16 ES	1	3/4	60	115	41,3	280
C16X6-16 ES	1	1	64	115	47,6	280
C20X6-16 ES	1	1 1/4	64	115	54	280
C20X6-20 ES	1 1/4	1 1/4	67,5	125	54	210
C24X6-20 ES	1 1/4	1 1/2	67,5	125	63,5	185
C24X6-24 ES	1 1/2	1 1/2	79,5	144	63,5	185
C32X6-32 ES	2	2	95	165	79,4	175

SAE 45° Flens 6000PSI uit een stuk type X645-ES (exclusief O-ring)



Modellen:

Bestelnummer	slangmaat	Flens	H	L	K	A	max. werkdruk bar*
C08X645-08 ES	1/2	1/2	47	80	20	31,8	415
C12X645-08 ES	1/2	3/4	53	86	26	41,3	415
C08X645-10 ES	5/8	1/2	51	87	21	31,8	350
C12X645-10 ES	5/8	3/4	57	93	26	41,3	350
C08X645-12 ES	3/4	1/2	64	104	26	31,8	350
C12X645-12 ES	3/4	3/4	64	104	26	41,3	280
C16X645-12 ES	3/4	1	68	108	31	47,6	350
C12X645-16 ES	1	3/4	79	130	31	41,3	280
C16X645-16 ES	1	1	80	131	32	47,6	280
C20X645-16 ES	1	1 1/4	85	136	37	54	280
C20X645-20 ES	1 1/4	1 1/4	93	151	37	54	210
C24X645-20 ES	1 1/4	1 1/2	99	157	43	63,5	210
C24X645-24 ES	1 1/2	1 1/2	111	175	55	63,5	185

Voor SAE afdichtringen zie pagina 3M.30

* Attentie: let ook op de maximale werkdruk van de slang.