



**NPT****NPTF MALE 60° CONE SEAT**  
*MASCHIO NPTF SVASATO 60°***AGN**

| TIEFFE<br>Part.N. | Hose Size |        |      | NPTF<br>Connection Size |      | Dimensions (mm) |     |    |  |  |  | Maximum<br>W.P. |      |
|-------------------|-----------|--------|------|-------------------------|------|-----------------|-----|----|--|--|--|-----------------|------|
|                   | DN        | Inch   | Dash | F                       | Dash | H               | L   | S  |  |  |  | bar             | PSI  |
| <b>CH1212NPT</b>  | 19        | 3/4"   | -12  | 3/4"-14                 | -12  | 34              | 98  | 27 |  |  |  | 280             | 4000 |
| <b>CH1216NPT</b>  | 19        | 3/4"   | -12  | 1"-11,5                 | -16  | 42              | 103 | 36 |  |  |  | 280             | 4000 |
| <b>CH1616NPT</b>  | 25        | 1"     | -16  | 1"-11,5                 | -16  | 42              | 115 | 36 |  |  |  | 280             | 4000 |
| <b>CH1620NPT</b>  | 25        | 1"     | -16  | 1 1/4"-11,5             | -20  | 45              | 118 | 46 |  |  |  | 210             | 3000 |
| <b>CH2020NPT</b>  | 31,5      | 1 1/4" | -20  | 1 1/4"-11,5             | -20  | 47              | 135 | 46 |  |  |  | 210             | 3000 |
| <b>CH2024NPT</b>  | 31,5      | 1 1/4" | -20  | 1 1/2"-11,5             | -24  | 50              | 137 | 50 |  |  |  | 185             | 2700 |
| <b>CH2424NPT</b>  | 38        | 1 1/2" | -24  | 1 1/2"-11,5             | -24  | 50              | 144 | 50 |  |  |  | 185             | 2700 |
| <b>CH3232NPT</b>  | 51        | 2"     | -32  | 2"-11,5                 | -35  | 55              | 153 | 60 |  |  |  | 175             | 2500 |

**MI****JIC MALE 37° CONE**  
*MASCHIO JIC CONO 37°***AGJ**

| TIEFFE<br>Part.N. | Hose Size |        |      | JIC 37°<br>Connection Size |      | Dimensions (mm) |     |    |  |  |  | Maximum<br>W.P. |      |
|-------------------|-----------|--------|------|----------------------------|------|-----------------|-----|----|--|--|--|-----------------|------|
|                   | DN        | Inch   | Dash | F                          | Dash | H               | L   | S  |  |  |  | bar             | PSI  |
| <b>CH1212MI</b>   | 19        | 3/4"   | -12  | 1 1/16"-12                 | -12  | 38              | 99  | 27 |  |  |  | 350             | 5000 |
| <b>CH1214MI</b>   | 19        | 3/4"   | -12  | 1 3/16"-12                 | -14  | 39              | 101 | 32 |  |  |  | 280             | 4000 |
| <b>CH1216MI</b>   | 19        | 3/4"   | -12  | 1 5/16"-12                 | -16  | 41              | 102 | 36 |  |  |  | 280             | 4000 |
| <b>CH1616MI</b>   | 25        | 1"     | -16  | 1 5/16"-12                 | -16  | 42              | 114 | 36 |  |  |  | 280             | 4000 |
| <b>CH1620MI</b>   | 25        | 1"     | -16  | 1 5/8"-12                  | -20  | 45              | 117 | 46 |  |  |  | 210             | 3000 |
| <b>CH2020MI</b>   | 31,5      | 1 1/4" | -20  | 1 5/8"-12                  | -20  | 47              | 134 | 46 |  |  |  | 210             | 3000 |
| <b>CH2024MI</b>   | 31,5      | 1 1/4" | -20  | 1 7/8"-12                  | -24  | 51              | 139 | 50 |  |  |  | 185             | 2700 |
| <b>CH2424MI</b>   | 38        | 1 1/2" | -24  | 1 7/8"-12                  | -24  | 52              | 145 | 50 |  |  |  | 185             | 2700 |
| <b>CH3232MI</b>   | 51        | 2"     | -32  | 2 1/2"-12                  | -32  | 63              | 160 | 65 |  |  |  | 175             | 2500 |