


## MM-S

### METRIC MALE - 24° CONE SEAT - HEAVY DUTY MASCHIO METRICO - SVASATO 24° - SERIE PESANTE

CES




| TIEFFE<br>Part.N. | Hose Size |        |      | METRIC 24°<br>Connection |      | Dimensions (mm) |     |    |  |  | Maximum<br>W.P. |      |
|-------------------|-----------|--------|------|--------------------------|------|-----------------|-----|----|--|--|-----------------|------|
|                   | DN        | Inch   | Dash | F                        | Pipe | H               | L   | S  |  |  | bar             | PSI  |
| CH12MM20S         | 19        | 3/4"   | -12  | M 30x2                   | 20S  | 31              | 93  | 30 |  |  | 420             | 6000 |
| CH12MM25S         | 19        | 3/4"   | -12  | M 36x2                   | 25S  | 35              | 97  | 36 |  |  | 420             | 6000 |
| CH16MM25S         | 25        | 1"     | -16  | M 36x2                   | 25S  | 36              | 109 | 36 |  |  | 380             | 5500 |
| CH16MM30S         | 25        | 1"     | -16  | M 42x2                   | 30S  | 40              | 113 | 46 |  |  | 380             | 5500 |
| CH20MM30S         | 31,5      | 1 1/4" | -20  | M 42x2                   | 30S  | 42              | 130 | 46 |  |  | 325             | 4700 |
| CH20MM38S         | 31,5      | 1 1/4" | -20  | M 52x2                   | 38S  | 46              | 134 | 55 |  |  | 325             | 4700 |
| CH24MM38S         | 38        | 1 1/2" | -24  | M 52x2                   | 38S  | 47              | 141 | 55 |  |  | 290             | 4200 |

## FOS-S

### METRIC FEMALE 24° O'RING CONE - HEAVY DUTY - SLIP-ON NUT FEMMINA METRICA OGIVA 24° O'RING - SERIE PESANTE - DADO LIBERO

DKOS



| TIEFFE<br>Part.N. | Hose Size |        |      | METRIC 24°<br>Connection |      | Dimensions (mm) |     |    |  |          | Maximum<br>W.P. |      |
|-------------------|-----------|--------|------|--------------------------|------|-----------------|-----|----|--|----------|-----------------|------|
|                   | DN        | Inch   | Dash | F                        | Pipe | H               | L   | S  |  | O-RING   | bar             | PSI  |
| CH12FOS20S        | 19        | 3/4"   | -12  | M 30x2                   | 20S  | 33              | 95  | 36 |  | 16,3x2,4 | 420             | 6000 |
| CH12FOS25S        | 19        | 3/4"   | -12  | M 36x2                   | 25S  | 36              | 98  | 46 |  | 20,3x2,4 | 420             | 6000 |
| CH16FOS25S        | 25        | 1"     | -16  | M 36x2                   | 25S  | 37              | 110 | 46 |  | 22x2     | 380             | 5500 |
| CH16FOS30S        | 25        | 1"     | -16  | M 42x2                   | 30S  | 39              | 112 | 50 |  | 25,3x2,4 | 380             | 5500 |
| CH20FOS30S        | 31,5      | 1 1/4" | -20  | M 42x2                   | 30S  | 41              | 128 | 50 |  | 25,3x2,4 | 325             | 4700 |
| CH20FOS38S        | 31,5      | 1 1/4" | -20  | M 52x2                   | 38S  | 43              | 131 | 60 |  | 33,3x2,4 | 325             | 4700 |
| CH24FOS38S        | 38        | 1 1/2" | -24  | M 52x2                   | 38S  | 44              | 138 | 60 |  | 33,3x2,4 | 290             | 4200 |