


**FIC**

**JIC FEMALE 37° CONE SEAT - DOUBLE EXAGON - TIEFFE NUT**  
*FEMMINA JIC SVASATA 37° - DOPPIO ESAGONO - DADO TIEFFE*

**DKJ**




Part.N.	Hose Size			JIC 37° Connection Size		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Dash	H	L	S	S1	bar	PSI	
CS1210FIC	19	3/4"	-12	7/8"-14	-10	33	84	27	27	350	5000	
CS1212FIC	19	3/4"	-12	1 1/16"-12	-12	34	85	32	27	350	5000	
CS1214FIC	19	3/4"	-12	1 3/16"-12	-14	35,5	86,5	36	30	280	4000	
CS1216FIC	19	3/4"	-12	1 5/16"-12	-16	38	89	41	32	280	4000	
CS1612FIC	25	1"	-16	1 1/16"-12	-12	36,5	93	32	32	350	5000	
CS1616FIC	25	1"	-16	1 5/16"-12	-16	39,5	96	41	32	280	4000	
CS1620FIC	25	1"	-16	1 5/8"-12	-20	46	102,5	50	41	210	3000	
CS2016FIC	31,5	1 1/4"	-20	1 5/16"-12	-16	45,5	112	41	41	280	4000	
CS2020FIC	31,5	1 1/4"	-20	1 5/8"-12	-20	48	114,5	50	41	210	3000	
CS2024FIC	31,5	1 1/4"	-20	1 7/8"-12	-24	51	117,5	60	46	185	2700	
CS2424FIC	38	1 1/2"	-24	1 7/8"-12	-24	53	135,5	60	46	185	2700	
CS2432FIC	38	1 1/2"	-24	2 1/2"-12	-32	66	148,5	75	60	175	2500	
CS3232FIC	51	2"	-32	2 1/2"-12	-32	69	165,5	75	60	175	2500	

**FIS45**

**JIC FEMALE 37° CONE SEAT - 45° ELBOW - TIEFFE NUT**  
*FEMMINA JIC SVASATA 37° - CURVA A 45° - DADO TIEFFE*

**DKJ45**



Part.N.	Hose Size			JIC 37° Connection Size		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Dash	H	L	K	S	bar	PSI	
CS1210FIS45	19	3/4"	-12	7/8"-14	-10	66	117	28	27	350	5000	
CS1212FIS45	19	3/4"	-12	1 1/16"-12	-12	63	114	25	32	350	5000	
CS1214FIS45	19	3/4"	-12	1 3/16"-12	-14	63	114	25	36	280	4000	
CS1216FIS45	19	3/4"	-12	1 5/16"-12	-16	66	117	28	41	280	4000	
CS1612FIS45	25	1"	-16	1 1/16"-12	-12	85	141	35	32	350	5000	
CS1616FIS45	25	1"	-16	1 5/16"-12	-16	82	138	32	41	280	4000	
CS1620FIS45	25	1"	-16	1 5/8"-12	-20	83	140	33	50	210	3000	
CS2016FIS45	31,5	1 1/4"	-20	1 5/16"-12	-16	100	167	41	41	280	4000	
CS2020FIS45	31,5	1 1/4"	-20	1 5/8"-12	-20	98	164	38	50	210	3000	
CS2024FIS45	31,5	1 1/4"	-20	1 7/8"-12	-24	99	165	39	60	185	2700	
CS2424FIS45	38	1 1/2"	-24	1 7/8"-12	-24	118	201	46	60	185	2700	
CS2432FIS45	38	1 1/2"	-24	2 1/2"-12	-32	122	204	50	75	175	2500	
CS3232FIS45	51	2"	-32	2 1/2"-12	-32	157	253	62	75	175	2500	