

FFI-2FFI Series



STANDARD series
NV - ANV - HVV - TNV

PUSH-PULL series
CPV - CNV

SCREW-ON series
CVV - PVM - WS

CHECK-VALVES series
VV - VUC

DIAGNOSTIC series
DF

FLAT-FACE series
FFI - 2FFI

MULTICONNECTION series
MULTIFASTER

GENERAL FEATURES

- **Connection system:** By pushing the male coupling
- **Disconnection system:** By pulling back the sleeve
- **Shut-off system:** Flat face Valve
- **Connection under pressure:** Not allowed
- **Disconnection under pressure:** Not allowed
- **Interchangeability:** According to ISO 16028 standards
- **Main application fields:** Building and Construction, Earth Moving



TECHNICAL DATA

Nominal Body Size		Working Pressure (*)	Flow Rate (**)	Burst Pressures (***)		
mm	inch			Connected	Male	Female
6,3	1/4"	32	20	160	130	
10	3/8"	27	70	150	110	
12,5	1/2"	25	100	140	100	
16	5/8"	27	120	140	110	
19	3/4"	27	160	120	110	
25	1"	25	210	110	100	

(*) Safety factor 1.4 (dynamic condition) applied on the minimum burst pressure

(**) Suggested flow rate (corresponding to 0,2 MPa pressure drop) with ISO VG32 hydraulic fluid

(***) 1 MPa = 145 PSI = 10 Bar

FURTHER INFORMATION

Test Specifications:
According to ISO 7241-2 standards


- Materials:**
- High grade carbon steel
 - Hardening treatment for specific stressed area
 - Standard seals in Nitrile Rubber (NBR) and Polyurethane
 - Back-up ring in PTFE
 - Zinc plating and CrIII passivation

Temperature Range:
from -25°C to +100°C (with standard seals)



The descriptions and illustrations in this catalogue are for information only and are not binding.

FFI-2FFI Series



FEMALE COUPLINGS

Nominal Body Size		Part Number (*)	Thread Size (A)	Length (B)	Sleeve (D)	Bulkhead Length	Hexagon (X)
mm	inch			mm	mm	mm	mm
6,3	1/4"	2FFI 14 GAS F	1/4" BSP Female	59	27	--	24
		2FFI 14 NPT F	1/4" NPTF Female	59	27	--	24
10	3/8"	2FFN 38 GAS F	3/8" BSP Female	73	30	--	27
		2FFN 38-12 GAS F	1/2" BSP Female	75	30	--	27
		2FFN 38 NPT F	3/8" NPTF Female	73	30	--	27
		2FFN 38-12 NPT F	1/2" NPTF Female	76	30	--	27
		2FFN 38-12 SAE F	3/4" UNF Female ORB	75	30	--	27
		2FFN 38-2/1815 F	M18x1,5 Male 12L	73	30	--	27
		2FFN 38-2/2215 F	M22x1,5 Male 15L	74	30	--	27
12,5	1/2"	2FFI 12 GAS F	1/2" BSP Female	82	38	--	32
		2FFI 12-34 GAS F	3/4" BSP Female	84	38	--	34
		2FFI 12 NPT F	1/2" NPTF Female	83	38	--	32
		2FFI 12-34 NPT F	3/4" NPTF Female	87	38	--	34
		2FFI 12-12 SAE F	3/4" UNF Female ORB	83	38	--	32
		2FFI 12-58 SAE F	7/8" UNF Female ORB	85	38	--	34
		2FFI 12-34 SAE F	1-1/16" UN Female ORB	87	38	--	34
16	5/8"	2FFI 12-12/58 S F	1" UNS Male Bulkhead ORFS	109	38	38	32
		2FFI 12-12/34 S F	1-3/16" UN Male Bulkhead ORFS	110	38	39	36
		2FFI 12-14/58 S F	7/8" UNF Male Bulkhead ORFS	112	38	42	34
19	3/4"	2FFI 12-14/34 S F	1-1/16" UN Male Bulkhead ORFS	116	38	45	34
		2FFI 34 GAS F	3/4" BSP Female	101	48	--	42
		2FFI 34-1 GAS F	1" BSP Female	101	48	--	42
		2FFI 34 NPT F	3/4" NPTF Female	101	48	--	42
		2FFI 34-34 SAE F	1-1/16" UN Female ORB	101	48	--	42
		2FFI 34-1 SAE F	1-5/16" UN Female ORB	102	48	--	42
		2FFI 34-12/34 S F	1-3/16" UN Male Bulkhead ORFS	131	48	41	42
25	1"	2FFI 34-14/34 S F	1-1/16" UN Male Bulkhead ORFS	135	48	44	42
		2FFI 1 GAS F	1" BSP Female	100	55	--	50
		2FFI 1-114G F	1-1/4" BSP Female	103	55	--	55
		2FFI 1 NPT F	1" NPTF female	100	55	--	50
		2FFI 1-1 SAE F	1-5/16" UN Female ORB	100	55	--	50

(*) Other part numbers are available on request, please contact FASTER Customer Service.

STANDARD series
NW - ANV - HNV - TNV

PUSH-PULL series
CPV - CNV

SCREW-ON series
CW - PWM - WVS

CHECK-VALVES series
WV - VUC

DIAGNOSTIC series
DF

FLAT-FACE series
FFI - 2FFI

MULTICONNECTION series
MULTIFASTER

The descriptions and illustrations in this catalogue are for information only and are not binding.

FFI-2FFI Series



STANDARD series
NV - ANV - HW - TNV

PUSH-PULL series
CPV - CNV

SCREW-ON series
CV - PWM - WS

CHECK-VALVES series
VU - VUC

DIAGNOSTIC series
DF

FLAT-FACE series
FFI - 2FFI

MULTICONNECTION series
MULTIFASTER

MALE COUPLINGS

Nominal Body Size		Part Number (*)	Thread Size (E)	Length (C)	Total Length (L) Connected	Diameter (H)	Bulkhead Length	Hexagon (Y)		
mm	inch			mm	mm	mm	mm	mm		
6,3	1/4"	FFI 14 GAS M	1/4" BSP Female	48	B + C - 11	16,1	--	24		
		FFI 14 NPT M	1/4" NPTF Female	48	B + C - 11	16,1	--	24		
10	3/8"	FFN 38 GAS M U	3/8" BSP Female	63	B + C - 16	19,7	--	27		
		FFN 38-12 GAS M U	1/2" BSP Female	67	B + C - 16	19,7	--	27		
		FFN 38 NPT M U	3/8" NPTF Female	63	B + C - 16	19,7	--	27		
		FFN 38-12 NPT M U	1/2" NPTF Female	67	B + C - 16	19,7	--	27		
		FFN 38-12 SAE M U	3/4" UNF Female ORB	67	B + C - 16	19,7	--	27		
		FFN 38-2/18 M U	M18x1,5 Male 12L	63	B + C - 16	19,7	--	27		
		FFN 38-2/22 M U	M22x1,5 Male 15L	64	B + C - 16	19,7	--	27		
		2FFN 38-7/1815 F	M18x1,5 Male Bulkhead Short 12L	78	B + C - 16	19,7	26	27		
		2FFN 38-7/2215 F	M22x1,5 Male Bulkhead Short 15L	78	B + C - 16	19,7	26	27		
12,5	1/2"	FFI 12 GAS M	1/2" BSP Female	79	B + C - 17	24,5	--	32		
		FFI 12-34 GAS M	3/4" BSP Female	84	B + C - 17	24,5	--	34		
		FFI 12 NPT M	1/2" NPTF Female	79	B + C - 17	24,5	--	32		
		FFI 12-34 NPT M	3/4" NPTF Female	84	B + C - 17	24,5	--	34		
		FFI 12-12 SAE M	3/4" UNF Female ORB	79	B + C - 17	24,5	--	32		
		FFI 12-58 SAE M	7/8" UNF Female ORB	84	B + C - 17	24,5	--	34		
		FFI 12-34 SAE M	1-1/16" UN Female ORB	84	B + C - 17	24,5	--	34		
				FFI 12-12/58 S M	1" UNS Male Bulkhead ORFS	104	B + C - 17	24,5	38	32
				FFI 12-12/34 S M	1-3/16" UN Male Bulkhead ORFS	105	B + C - 17	24,5	39	36
				FFI 12-14/58 S M	7/8" UNF Male Bulkhead ORFS	106	B + C - 17	24,5	40	34
		FFI 12-14/34 S M	1-1/16" UN Male Bulkhead ORFS	110	B + C - 17	24,5	44	34		
16	5/8"	FFI58-34 GAS M	3/4" BSP Female	93	B + C - 18	27	--	38		
		FFI58-34 SAE M	1-1/16" UN Female ORB	93	B + C - 18	27	--	38		
19	3/4"	FFI 34 GAS M	3/4" BSP Female	100	B + C - 22	29,9	--	42		
		FFI 34-1 GAS M	1" BSP Female	102	B + C - 22	29,9	--	42		
		FFI 34 NPT M	3/4" NPTF Female	100	B + C - 22	29,9	--	42		
		FFI 34-34 SAE M	1-1/16" UN Female ORB	100	B + C - 22	29,9	--	42		
		FFI 34-1 SAE M	1-5/16" UN Female ORB	100	B + C - 22	29,9	--	42		
				FFI 34-12/34 S M	1-3/16" UN Male Bulkhead ORFS	127	B + C - 22	29,9	41	42
		FFI 34-14/34 S M	1-1/16" UN Male Bulkhead ORFS	131	B + C - 22	29,9	44	42		
25	1"	FFI 1 GAS M	1" BSP Female	108	B + C - 22	36	--	50		
		FFI 1-114G M	1-1/4" BSP Female	111	B + C - 22	36	--	55		
		FFI 1 NPT M	1" NPTF female	108	B + C - 22	36	--	50		
		FFI 1-1 SAE M	1-5/16" UN Female ORB	108	B + C - 22	36	--	50		

(*) Other part numbers are available on request, please contact FASTER Customer Service.

ACCESSORIES

Nominal Body Size		Dust protections for male couplings			Dust protections for female couplings			Spare parts kits Male	Spare parts kits Female
		PVC (*)		Aluminium	PVC (*)		Aluminium		
mm	inch	Part Number	Colour	Part Number	Part Number	Colour	Part Number		
6,3	1/4"	TM 2FI14	ORANGE	TM 2FI14 S	TF 2FI14	ORANGE	TF 2FI14 S	KIT 2FFI14 M	KIT 2FFI14 F
10	3/8"	TMF 38	ORANGE	TM 2FN38 S	TFF 38	ORANGE	TF 2FN38 S	KIT 2FFN38 M	KIT 2FFN38 F
12,5	1/2"	TM 2FI12	ORANGE	TM 2FI12 S	TF 2FI12	ORANGE	TF 2FI12 S	KIT 2FFNP12 M	KIT 2FFI12 F
16	5/8"	TM 2FI58	ORANGE	TM 2FI58 S	TF 2FI58	ORANGE	TF 2FI58 S	KIT FFI58 M	KIT 2FFI58 F
19	3/4"	TM 2FI34	ORANGE	TM 2FI34 S	TF 2FI34	ORANGE	TF 2FI34 S	KIT FFI34 M	KIT 2FFI34 F
25	1"	TM 2FI1	ORANGE	TM 2FI1 S	TF 2FI1	ORANGE	TF 2FI1 S	KIT 2FFNP1 M	KIT 2FFI1 F

(*) Other colours are available on request, please contact FASTER Customer Service.

The descriptions and illustrations in this catalogue are for information only and are not binding.